

CLAIMS - - I claim:

1. A folding tie, comprising:

- a) a foldable support element having a plurality of opposing major sides;
- b) at least two male fastening members on said opposing major sides of said support element, respectively; and
- c) at least two female fastening members on said opposing major sides of said support element, respectively; whereby, when said support element is folded, at least one of said female fastening members, will be detachably joined to at least one of said female fastening members to form a releasable couple.

2. The folding tie of Claim 1, further including a label surface on one of said opposing major sides of said tie.

3. The folding tie of Claim 1 wherein said fastening members comprise hook-and-loop touch-surface fasteners.

10076275.024403  
204120" 52200T

4. The folding tie of Claim 1 further including;

a) at least one discontinuity between segments of said support element;

and

b) at least one spanning element, spanning said discontinuity, and  
interconnecting said segments of said support element.

5. A method for managing at least one moveable article, comprising:

a) providing at least one folding tie, said tie including a foldable  
support element having a plurality of opposing major sides  
and having at least two male fastening members on said  
opposing major sides of said support element, respectively,  
and having at least two female fastening members on said  
opposing major sides of said support element, respectively;  
and

b) folding said support element around said moveable article  
for detachably connecting at least one of said male fastening  
members to at least one of said female fastening members for  
providing a releasable couple which holds said support

10076275.024402

element in folded form around said moveable article, thereby to enfold and hold said article to effect organization and detachable securement thereof.

6. The method of Claim 5 wherein said male and female fastening members comprise hook-and-loop touch-surface fasteners.

7. The method of Claim 5, further including a label surface on one of said major sides of said tie.

8. The method of Claim 5, further including;

a) at least one discontinuity between segments of said support element; and

b) at least one spanning element, spanning said discontinuity and interconnecting said segments of said support element.

9. A folding tie, comprising:

- a) a foldable support element having a plurality of opposing major sides;
- b) said support element having at least two arms radiating from a common point; and
- c) at least two male fastening members on said opposing major sides of said support element, respectively; and
- d) at least two female fastening members on said opposing major sides of said support element, respectively; whereby, when said support element is folded, said one of said male fastening members will be detachably connected to said one of said female fastening members to form a releasable couple.

10. The folding tie of Claim 9 wherein said arms are furcated.

11. The folding tie of Claim 9, further including a label surface on one of said major sides of said tie.

12. The folding tie of Claim 9 wherein said male and female fastening members comprise hook-and-loop touch-surface fasteners.

13. The folding tie of Claim 9 further including;

- a) at least one discontinuity between segments of said support element;  
and
- b) at least one spanning element, spanning said discontinuity, and  
interconnecting said segments of said support element.

14. A folding tie, comprising:

- a) a sheet-like foldable support element having a plurality of  
opposing major sides;
- b) each of said major sides of said support element having at  
least two male fastening members on said opposing sides of  
said support element, respectively; and
- c) each of said major sides of said support element having at  
least two female fastening members on said opposing sides of  
said support element, respectively; whereby, when said

10076275-024402  
2017-02-22

support element is folded, said one of said male fastening members will be detachably connected to said one of said female fastening members to form a releasable couple.

15. The folding tie of Claim 14, further including a label surface on one of said opposing major sides of said tie.

16. The folding tie of Claim 14 wherein said male and female fastening members comprise hook-and-loop touch-surface fasteners.

17. A folding tie, comprising:

- a) a foldable support element having a plurality of opposing major sides;
- b) at least one of said opposing major sides of said support element conveying an image; and
- c) at least two male fastening members on said opposing major sides of said support element, respectively; and
- d) at least two female fastening members on said opposing

major sides of said support element, respectively; whereby, when said support element is folded, said one of said male fastening members will be detachably connected to said one of said female fastening members to form a releasable couple.

18. The tie of Claim 17, further including a label surface on one of said opposing major sides of said tie.

19. The tie of Claim 17 wherein said male and female fastening members comprise hook-and-loop touch-surface fasteners.

20. The tie of Claim 17, further including a decorative component on at least one of said major opposing sides of said tie.